



EPI-LX-R-1000 [1]			
L	120 VAC, 60Hz		
N	5.5 A		
GND			
1A	Total Length	Amps	Watts
	19 ft	7.2 A	171 W
2A	Total Length	Amps	Watts
	24.5 ft	9.2 A	220.5 W
N			
N			
1B	Total Length	Amps	Watts
	15.75 ft	6 A	141.75 W
2B	Total Length	Amps	Watts
	13.5 ft	5.2 A	121.5 W
N			
N			
1C	Total Length	Amps	Watts
2C	Total Length	Amps	Watts
N			
N			

Recommended Spacing Between Strips:	
Tile, Natural Stone, Resilient	2 - 3 inches
Hardwood, Laminate	2 - 5 inches
Carpet	2 - 8 inches

Job ID:	123456 (Rev. 1)
Date:	20-Apr-2007
Company:	John Doe Contracting, Inc.
Project:	Example Project - Master Bath
Area To Be Heated:	Master Bathroom

- Notes:**
- All power supplies are to be HARDWIRED
 - Use TWO WIRE COLORS (e.g. black and white) to differentiate polarities
 - Installation according to NEC article 424.90 through 99
 - Service Panel: Use HID (HIGH INTENSITY DISCHARGE) circuit breaker or equivalent